



DEUTSCH DTM SEALED FLANGE RECEPTACLE

TE Connectivity's (TE) new DEUTSCH DTM sealed flange receptacle simplifies wire routing and assembly in applications that require mounted connections. It is available with an optional seal that provides environmental protection and allows the designer the ability to assemble the connectors on the outside of a through hole application, such as a battery package.

Features

- Housing with integrated flange
- Optional flange seal

Applicable Documents

- Product Specification: 108-151010
- Application Specification: 114-151003

Description	Flange Sealed	Connector Part No.	Material	Colour	Mating Terminal	Terminal Part No.	Wire Range (mm ²)	Wire Insulation Diameter (mm)
DTM12P Through Hole Connector	Y	1-2303064-1/2/3/4	PA66-GF15	Grey	DEUTSCH #20	1060-20-01XX	0.35-1.5	1.91-3.18
	N	2303064-1/2/3/4				1060-20-02XX	0.35-1.5	1.30-2.16
						1060-20-06XX	1.0-2.5	1.91-3.18

Plating (XX): 22 = Nickel, 44 = Gold, 77 = Tin

Specifications

Contact Resistance	12.5Mohm Max
Insulation Resistance	1000Mohm
Contact	DEUTSCH #20
Temperature Range	-55°C to 125°C
Degree of Protection	IP67 and IP6K9K (with rear protection)

TE TECHNICAL SUPPORT CENTER

USA: +(1) 800.522.6752

Canada: +(1) 905.475.6222

China: +(86) 400.820.6015

France: +(33) 1.3420.8686

Germany: +(49) 6251.133.1999

India +(91) 80.285.40800

UK: +(44) 8706.080.208

www.te.com/ict

While TE Connectivity has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice.

TE Connectivity, TE connectivity (logo) and DEUTSCH are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.
©2017 TE Connectivity All Rights Reserved.